

**Dual lens Smart Wifi Camera:HD9013-WF-SL**

- \* Smart AI function:human detection,human tracking,intrusion detection,line crossing alarm
- \* Dual light, warn light enable when detect human.
- \* Two way audio , audio broadcast
- \* Support both cloud storage and TFcard storage
- \* Easy wifi connection, support both wired and wifi connection



Specs	
DSP	ST377+200AI+400AI
Sensor	PTZ camera
	1/2.8 CMOS 4.0MP
Video output	2304*1296
Lens	36倍 5.35-96.3mm
VOA	W:53.9°; P: 44.3°; T:33.9° Tele :9°; P: 7.8°; T:5.8°
DNR	2DNR,3DNR
Aperture	F1.8~F2.5
Image setting	auto W/B /AE/ BLC/ DWDR/ Digital anti-fog/ anti-flash
Video compression	H.265AI dual stream ,AVI ; bitrate 0.1M~10Mbps adjustable ; fram rate 1~30 fp/s adjustable
Audio	Two way audio, build in Mic and speaker
Preset Points	Support preset setting
Tour	Support 1 tour ( max 1-16 presets)
Rotation Speed	Pan 270° , 22°/S , Tilt 90° , 15°/s
AI function	human detection,human tracking,intrusion detection,line crossing alarm
Alarm linkage	TF card local video recording , APP push alarm , sound and light alarm
APP	Seetong, Support Android、IOS mobile remote management
Operation menu	Multi language, English, German, Spanish, French,Italian, Japanese, Korean, Polish, Portuguese, Russian, Thai, Turkish, Vietnamese, Simplified Chinese, Traditional Chinese
Communications Protocol	RTSP/FTP/DHCP/NTP/UPnP/( not support onvif, can connected to the XM NVR)
Wired connector	RJ45 connector , 10/100M adaptive
WiFi connector	Wifi connection, 2.4 GHz
IR distance	Up to 150meters
Warm light distance	Up to 150meters
LEDs	9pcs Dual Wick Lamps ( fixed camera ) 2pcs IR+9pcs warm light ( PTZ camera )
Light mode	Colorful Mode, IR Mode, Intellegent Mode
Factory default	Support button reset
Operating temperature	-25℃~+50℃
Power	12V DC
Consumption	≤20W

Housing	Metal
Dimension	26*26*43CM 3.8KG 1\Pcs 55*28*46CM 8.5KG 2\Pcs
Weight	Product: 3KG Gw:3.8KG
Accessories	Water proof cap, Screw pack x1, Manualx1



